

ZERO BEZEL TOUCH TABLE

True Flat 40" / 46" / 55" Interactive Touch Table



Applications

| Corporate | Retail | Reception | Exhibitions
| Training & Education | Product Presentation

Features

- Attractive flat front surface with black border and brushed stainless steel surround
- Fast, accurate projective capacitive touch technology
- Detects up to 40 independent touch points with palm rejection
- 40", 46" & 55" professional full HD 1080p LED display
- 4mm thick, anti-glare smooth travel tempered glass surface
- Works in any lighting environment
- Choice of bar or coffee height tables
- Equipped with a powerful PC & Windows 8 installed
- Lima multitouch interactive software fully installed
- Customised versions available including choice of: paint colour, logo, finish, printed border, thickness and size of glass, number of touch points, PC specifications and peripherals

Specifications - Zero Bezel Touch Table

Model	ZBT40-10	ZBT46-10	ZBT55-10
Display			
Size	40" (101.6cm)	46" (117.0cm)	54.5" (138.8cm)
Type	S-PVA with LED backlights	S-PVA with LED backlights	S-PVA with LED backlights
Viewing Area [mm]	885.6 x 498.2	1018.1 x 572.7	1209.6 x 680.4
Brightness [cd/m2]	630max (with touch sensor fitted)	630max (with touch sensor fitted)	630max (inc touch sensor fitted)
Contrast Ratio	3500:1	4000:1	4000:1
Viewing Angle	178° Horizontal/ 178° Vertical	178° Horizontal/ 178° Vertical	178° Horizontal/ 178° Vertical
Horizontal Frequency [kHz]	31.5 - 91.1 (Analog & Digital)	31.5 - 91.1 (Analog & Digital)	31.5 - 91.1 (Analog & Digital)
Vertical Frequency [Hz]	50 - 85	50 - 85	50 - 85
Native Resolution	1920 x 1080 @ 60Hz	1920 x 1080 @ 60Hz	1920 x 1080 @ 60Hz
Remote Control	IR wireless	IR wireless	IR wireless
Touch Sensor			
Detection	Projective Capacitive Technology (PCT™), mutual capacitive type	Projective Capacitive Technology (PCT™), mutual capacitive type	Projective Capacitive Technology (PCT™), mutual capacitive type
Sensor	4mm thick, anti glare, tempered glass with embedded micro-fine sensing array. Hardness - Mohs 7	4mm thick, anti glare, tempered glass with embedded micro-fine sensing array. Hardness - Mohs 7	4mm thick, anti glare, tempered glass with embedded micro-fine sensing array. Hardness - Mohs 7
Stylus	Finger, gloved hand, conductive stylus	Finger, gloved hand, conductive stylus	Finger, gloved hand, conductive stylus
Touch Points	Detects up to 40 independent	Detects up to 40 independent	Detects up to 40 independent
PC (built-in)			
Processor	Intel Core i5-4430 (64MB Cache, up to 3.2GHz with Turbo Boost Technology)	Intel Core i5-4430 (64MB Cache, up to 3.2GHz with Turbo Boost Technology)	Intel Core i5-4430 (64MB Cache, up to 3.2GHz with Turbo Boost Technology)
Operating System	Windows 8 64bit, English	Windows 8 64bit, English	Windows 8 64bit, English
Video Card	1GB GDDR NVIDIA® GeForce® GTX 645	1GB GDDR NVIDIA® GeForce® GTX 645	1GB GDDR NVIDIA® GeForce® GTX 645
Memory	8GB Dual Channel DDR3 at 1600Mhz	8GB Dual Channel DDR3 at 1600Mhz	8GB Dual Channel DDR3 at 1600Mhz
Hard Drive	1TB (64MB Cache) 7200 RPM SATA 3Gb/s	1TB (64MB Cache) 7200 RPM SATA 3Gb/s	1TB (64MB Cache) 7200 RPM SATA 3Gb/s
CD ROM/DVD ROM	Slot-Loading Dual Layer DVD Burner (DVDRW, CD-RW)	Slot-Loading Dual Layer DVD Burner (DVDRW, CD-RW)	Slot-Loading Dual Layer DVD Burner (DVDRW, CD-RW)
Wireless	DW1506 Wireless-N WLAN Half Mini-Card	DW1506 Wireless-N WLAN Half Mini-Card	DW1506 Wireless-N WLAN Half Mini-Card
Audio Output	Built in Speakers (15W + 15W)	Built in Speakers (15W + 15W)	Built in Speakers (15W + 15W)
Power Requirements [AC]	100 - 120V/ 220 - 240V	100 - 120V/ 220 - 240V	100 - 120V/ 220 - 240V
Power Consumption [w]	565 (max)	585 (max)	635 (max)
Temperature (operating) [°C]	+10 to +35	+10 to +35	+10 to +35
Relative Humidity (operating) [%]	20 to 80 (non-condensing)	20 to 80 (non-condensing)	20 to 80 (non-condensing)
Approval	CE	CE	CE
Standard Options	Software Installed (Lima, Anti Virus, MS Office), DVI output cable, RJ45 cable, side USB input, Intel Core i7 processor, coffee or bar height table	Software Installed (Lima, Anti Virus, MS Office), DVI output cable, RJ45 cable, side USB input, Intel Core i7 processor, coffee or bar height table	Software Installed (Lima, Anti Virus, MS Office), DVI output cable, RJ45 cable, side USB input, Intel Core i7 processor, coffee or bar height table

REV R3A